

Service
Service
Service



Philips Domestic Appliances and Personal Care

Service Manual

PRODUCT INFORMATION

- Maximum air displacement : 30 l/sec
- Maximum vacuum water column : 300 cm
- Power consumptio (IEC) 225V : 1300 W
- Dust storage capacity : 2 litres
- Cord length (depends on version) : 5.3 m
- Filter system : 5 filters
- Dimensions cleaner : 37 x 28 x 23 cm
- Weight accessoires : 4.8 kg
- Noise : 80 dB max.
- Colour : Coral red
- Electronic controlled motor rpm
- Cordwinder build-in with flat cord
- Dustbag-full indicator in dustcover

OPTIONAL

Exhaust air filter	FC 8032 (4822 015 70056)
S-cotton dustbag	HR 6997 (4822 480 10115)
S-paper dustbags	FC 8021 (4822 480 10113)
Clinic dustbags	FC 8022 (8838 022 01010)

SERVICE INFORMATION

- To open the appliance, first remove the screws A,B,C,D.
- To reach the motor remove the screws E.
- To disassemble the cordwinder use Torx screw driver no T10, which is one of set consisting of T20, T15, T10, T9, T8, T7 and T6 = 4822 395 50145.
- Give attention that the contact fingers (item 45) are placed on the cord-winder shaft in such a way that the pressure point of the cordwinder knob to the cord winderlever (item 40) is vertical.
- The spare parts have been standardized as much as possible.
- Component configuration on exploded view may differ in case of specific versions, however, the actual components are distinguished by means of code numbers.
- Item 1 Cotton dustbag is used in those countries where paper dustbags are not available
- Item 41 Cord-winder spring unit is provided with a long spring, both long and short cords can be used in combination with this spring.
- Cordwinder spring has to be tensioned till maximum minus approx. 1,5 revolution.

This product meets the requirements regarding interference suppression on radio and TV.

After the product has been repaired, it should function properly and has to meet the safety requirements as officially laid down at this moment.

Pos.	12 nc	description		Pos.	12 nc	description	
1	4822 480 10115	S-cotton dustbag	HR 6997 (opt.)	40	4322 003 06620	push rod	
	8838 022 01010	Clinic dustbags	FC 8022 (opt.)	41	4322 009 07610	reelhalf springside	
	4822 480 10113	S-paper dustbags	FC 8021	42	4322 001 72360	brake tyre	
2	4322 009 07670	dustbag holder	(grey)	43	4322 009 07640	base plate	
3	4322 009 08520	upperhousing (el.)		44	4322 009 07620	reelhalf contactside	
4	4322 001 73150	inletrubber		45	4322 009 07630	contact plate	
5	4322 003 17250	nose piece		46	4322 006 01880	Argentina	L = 6.3 m
6	4322 001 99290	wheel (24)			4322 006 01380	Australia	L = 6.3 m
7	4322 002 22260	spindle		47	4322 006 01770	Japan / Taiwan	L = 5.3 m
8	4322 009 08510	lower housing		48	4322 006 01370	H.K. / U.K.	L = 6.3 m
9	4322 003 21130	handle el.	(coral red)	49	4322 006 01400	Euro 4.8 mm	L = 6.3 m
10	4322 009 08580	vario knob		50	4322 006 01480	Swiss	L = 6.3 m
11	4322 009 08550	dust cover	(coral red)	51	4322 006 01430	Italy	L = 6.3 m
12	4322 001 72900	motor buffer		54	4341 004 20100	small nozzle	
13	4322 001 73160	sealing m.c.		55	4341 003 00240	tube clip	
14	4322 000 35360	duo filter		56	4322 002 22610	steel tube con. 55 cm.	
14A	4322 009 08460	duo filter and holder		57	4341 004 20420	bend + hose	
15	4322 003 17740	hinge	(grey)	58	4341 005 01240	bend handle	
16	4322 009 07730	cord outlet		59	4341 004 20170	crevice nozzle	
17	4322 003 17320	backgrille	(grey)	60	4322 004 21180	nozzle D272	
18	4822 015 70056	exhaust filter		61	4822 479 20039	nozzle brush	
19	4322 009 08500	rear wheel		62	4822 479 20038	nozzle strip	
20	4322 003 21180	knobs	(coral red)	63	4322 003 10020	clip telescopic tube	(opt.)
21	4322 000 09750	pedal spring		64	4322 004 21050	telescopic tube	(opt.)
22	4322 006 20080	Low Volt PCB					
	4322 006 22210	High Volt PCB					
22A	4322 006 50600	switch (soldered version)					
23	4322 001 73230	cooling connection					
24	4322 003 21030	motor cap	(grey)				
25	4322 001 72780	buffer ring front					
26	4322 006 97400	motor 110 V - 60 Hz / ans					
	4322 009 06430	motor 220 - 240 V / ans					
28	4322 009 07520	motor foam/disc/ans					







